

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)

03-01-2003

2. REPORT TYPE

Abstract

3. DATES COVERED (From - To)

4. TITLE AND SUBTITLE

Synthesis and Atomic Oxygen Erosion Testing of Space-Survivable POSS (Polyhedral Oligomeric Silsesquioxane) Polyimides

5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)

Sandra J. Tomczak¹

Gar B. Hoflund²

5d. PROJECT NUMBER

2303

5e. TASK NUMBER

0026

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

¹Air Force Research Laboratory (AFMC)
AFRL/PRSM
10 E. Saturn Blvd.
Edwards AFB, CA 93524-7680

²Department of Chemical Engineering
University of Florida
Gainesville, FL 32611

8. PERFORMING ORGANIZATION
REPORT NUMBER

AFRL-PR-ED-AB-2002-312

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

10. SPONSOR/MONITOR'S
ACRONYM(S)

11. SPONSOR/MONITOR'S
NUMBER(S)

AFRL-PR-ED-AB-2002-312

12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

20030213 109

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:

17. LIMITATION
OF ABSTRACT

18. NUMBER
OF PAGES

19a. NAME OF RESPONSIBLE
PERSON

Leilani Richardson

a. REPORT

b. ABSTRACT

c. THIS PAGE

Unclassified

Unclassified

Unclassified

A

19b. TELEPHONE NUMBER
(include area code)
(661) 275-5015

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. Z39.18

MEMORANDUM FOR PRS (In-House/Contractor Publication)

16 Dec 2002

FROM: PROI (STINFO)

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-AB-2002-312**
SV Gonzalez, Rene I.; et al., "Synthesis and Atomic Oxygen Erosion Testing of Space-Survivable POSS
(Polyhedral Oligomeric Silsesquioxane) Polyimides"

9th International Symposium on Materials in a Space Environment
(ESTEC, Noordwijk, The Netherlands, 16-20 June 2003) (Deadline: 5 Jan 2003)

(Statement A)

Submitted for an ORAL Presentation

**Synthesis and Atomic Oxygen Erosion Testing of Space-Survivable
POSS (Polyhedral Oligomeric Silsesquioxane) Polyimides**

Rene I. Gonzalez¹, Sandra J. Tomczak¹, Gar B. Hoflund², Timothy K. Minton³ and Amy Brunsvold³. (1) AFRL/PRSM, Materials Applications Branch, Air Force Research Laboratory, 10 E. Saturn Blvd, Bldg. 8451, Edwards AFB, CA 93524, Tel: (661) 275-5252, Fax: (661)-275-5471, rene.gonzalez@edwards.af.mil, (2) Department of Chemical Engineering, University of Florida, Gainesville, FL 32611 (3) Department of Chemistry and Biochemistry, Montana State University, 108 Gaines Hall Bozeman, MT 59717

Keywords: atomic oxygen, AO, POSS, polymer, erosion, passivation, Kapton replacement, Silsesquioxane, Polyimide, Space

The harsh environment present in both Low-Earth and Geosynchronous Orbit (LEO and GEO) combined with the need for lighter weight and lower cost man-made orbiting bodies necessitates the design of multi-functional, space-survivable materials. Over the last two decades it has been well established that conventional polymers used in the construction of space vehicles undergo severe degradation resulting in reduced spacecraft lifetimes. In particular the polyimide Kapton has been studied at length since it is widely used as a flexible substrate for lightweight high power solar arrays because of its inherent strength and desirable thermal properties. In addition to Kapton, thin films of fluorinated polymers such as Teflon FEP are used as the outer layer of multi-layer thermal control insulation because of their superior optical properties, including low solar absorptance and high thermal reflectance. These polymeric materials degrade because spacecraft surfaces must endure a high incident fluences of atomic oxygen (AO), bombardment by low and high-energy charged particles, and thermal cycling along with the full spectrum of solar radiation.

Hybrid inorganic/organic polymers have the potential to meet the requirements of space-survivable materials by bridging the gap between ceramics and plastics, resulting in the prevention of AO and radiation damage that has hampered the widespread application of organic polymers in space. The Polymer Working Group at the Air Force Research Laboratory at Edwards AFB has incorporated inorganic POSS (Polyhedral Oligomeric Silsesquioxane) frameworks into traditional polymer systems resulting in hybrid POSS-polymers with dramatic

property enhancements. Addition of these POSS nanostructured frameworks into polymers results in increased use and decomposition temperatures, improved mechanical properties, and oxidation resistance. These nanoscopic POSS frameworks are comprised of a three dimensional inorganic core with a 3:2 O-Si ratio. They may be functionalized with a polymerizable group or groups and are surrounded by inert organic groups at the remaining vertices. These nonreactive organic groups (cyclopentyl, cyclohexyl, phenyl, isobutyl, methyl) aid in the compatibilization of the POSS macromers within the polymer matrix.

Our previous research has shown that POSS nanostructures can be easily dispersed throughout the polymer matrix by chemical manipulation of these inert organic groups surrounding the POSS cage. This has allowed us to synthesize completely transparent materials at high POSS loadings. We have also shown that polymers containing POSS rapidly form a ceramic-like, passivating and self-healing silica layer when exposed to high incident fluxes of AO. We believe that this self-healing nature is a direct result of POSS compatibility and dispersion throughout the polymer matrix. If the resultant glassy silica layer erodes or suffers a microdefect, it would quickly reform due to the uniform POSS dispersion. This process potentially prolongs the lifetime of the material in space therefore extending the time between repairs of spacecraft surfaces. This talk presents several characterization studies of the surfaces of newly synthesized POSS-containing polymers, specifically polyimides before and after exposure to AO. Atomic oxygen exposure testing was conducted independently at the University of Florida and Montana State University revealing comparable data. A variety of POSS-containing copolymers were examined because they have diverse properties and might perform well in different space-related applications. The exposed surfaces were characterized using X-ray photoelectron spectroscopy, and atomic oxygen erosion rates were calculated using stylus surface profilometry. Experiments were carried out in-situ because air exposure modifies the reactive surfaces formed during exposure to AO. The data indicates that just a 10 wt% (1 mole %) addition of POSS in a kapton-like polyimide can result in over a tenfold improvement in the AO erosion rate while a 20 wt% addition results in over a twentyfold improvement. These high-performance, self-healing POSS polyimides are a revolutionary step forward in space-survivable materials and should enable the long-term deployment of space inflatable structures and membranes for antennas, solar arrays and solar sails.